



# FLOORING ADHESIVES

A RANGE OF HIGH PERFORMANCE FLOORING ADHESIVES  
DESIGNED FOR TODAY'S FLOORCOVERINGS





The ARDEX range of High Performance Flooring Adhesives has been developed and tested to be fully compatible with today's most popular floorcoverings; offering the professional installer unique application benefits and guaranteed long term performance, helping to ensure the perfect installation every time.

All ARDEX Flooring Adhesives are designed to work with our complete range of Levelling and Smoothing Compounds in both commercial and domestic environments.

## REPAIR




REPAIR MORTARS

## PROTECT



MOISTURE CONTROL  
& PRIMING

## LEVEL & SMOOTH



LEVELLING AND  
SMOOTHING COMPOUNDS

## INSTALL



FLOORING ADHESIVES

ARDEX Flooring Adhesives meet the requirement guidelines for the EMICODE licence, achieving the lowest possible emission limits.



# ARDEX RECOMMENDED ADHESIVES GUIDE

All ARDEX Flooring Adhesives are designed to work with our complete range of Levelling and Smoothing Compounds, in both commercial and domestic environments, and have been developed and tested to be fully compatible with today's most commonly used floorcovering types.

ARDEX Flooring Adhesives meet the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.



**Our quick reference guide allows you to easily identify the most appropriate adhesive for the floorcovering you are installing.**

| PAGE | DESCRIPTION                 | PRODUCT            | PACK SIZE | VINYL                        |              |             |           |                   |                        | LINOLEUM              |                        |                        |
|------|-----------------------------|--------------------|-----------|------------------------------|--------------|-------------|-----------|-------------------|------------------------|-----------------------|------------------------|------------------------|
|      |                             |                    |           | LUXURY VINYL TILE AND PLANKS | LOOSELAY LVT | VINYL SHEET | CUSHIONED | COVING / SKIRTING | VINYL COMPOSITION TILE | JUTE / HESSIAN BACKED | POLYESTER BACKED SHEET | POLYESTER BACKED TILES |
| 6    | PRESSURE SENSITIVE VINYL    | ARDEX AF 145       | 12kg      | ✓                            |              | ✓           | ✓         |                   | ✓                      |                       |                        |                        |
| 8    | PRESSURE SENSITIVE CONTRACT | ARDEX AF 148       | 10kg      | ✓                            |              | ✓           | ✓         |                   | ✓                      |                       |                        |                        |
| 10   | VINYL                       | ARDEX AF 165       | 14kg      |                              |              | ✓           | ✓         |                   |                        |                       |                        |                        |
| 12   | LUXURY VINYL TILE           | ARDEX AF 175       | 6kg/12kg  | ✓                            |              |             | ✓         |                   | ✓                      |                       |                        |                        |
| 14   | LOW EMISSION CARPET         | ARDEX AF 325       | 14kg      |                              |              |             |           |                   |                        |                       |                        |                        |
| 16   | TACKIFIER                   | ARDEX AF 825       | 10kg      |                              | ✓            |             |           |                   |                        |                       |                        |                        |
| 18   | HIGH GRAB TACKIFIER         | ARDEX AF 835       | 10kg      |                              | ✓            |             |           |                   |                        |                       |                        |                        |
| 20   | HEAVY DUTY (ONE COMPONENT)  | ARDEX AF 2575 PLUS | 7kg       | ✓                            |              | ✓           |           |                   | ✓                      |                       |                        |                        |
| 22   | HEAVY DUTY (TWO COMPONENT)  | ARDEX AF 2525 2K   | 6kg       | ✓                            |              | ✓           |           |                   | ✓                      |                       |                        |                        |
| 24   | UNIVERSAL                   | ARDEX AF 2365      | 6kg/14kg  | ✓                            |              | ✓           | ✓         |                   | ✓                      | ✓                     | ✓                      | ✓                      |
| 26   | SOLVENT FREE CONTACT        | ARDEX AF 635       | 2.5kg     | ✓<br>††                      |              | ✓<br>††     | ✓<br>††   | ✓<br>††           | ✓<br>††                | ✓<br>††               | ✓<br>††                | ✓<br>††                |
| 28   | RUBBER                      | ARDEX AF 275       | 12kg      |                              |              |             |           |                   |                        |                       |                        |                        |
| 30   | LINOLEUM                    | ARDEX AF 785       | 14kg      |                              |              |             |           |                   |                        | ✓                     | ✓                      | ✓                      |

## FEATURED ADHESIVE:

### HEAVY DUTY ADHESIVE - ONE COMPONENT



- Moisture, weather and water resistant
- Suitable for internal and external use
- High temperature resistance, ideal for use in areas of direct sunlight and with underfloor heating systems
- Very high bond strength, for use in high load areas
- Zero waste – ready mixed and resealable
- Very low emissions
- Solvent free
- Suitable for installing LVT to walls
- Covers up to 23m<sup>2</sup>

| CARPET |           |          |                           |                  |      |       |     |                  |                | CARPET TILES   |     |            | UNDERLAY        |  | RUBBER          |                 |                 |
|--------|-----------|----------|---------------------------|------------------|------|-------|-----|------------------|----------------|----------------|-----|------------|-----------------|--|-----------------|-----------------|-----------------|
| WOVEN  | ACTIONBAC | GEL FOAM | NEEDLEPUNCH / FIBREBONDED | SECONDARY BACKED | FELT | LATEX | PVC | ARTIFICIAL GRASS | NATURAL FIBERS | BITUMEN BACKED | PVC | GEL BACKED | CARPET UNDERLAY |  | SHEET UP TO 4mm | TILES UP TO 4mm | TILES ABOVE 4mm |
|        |           |          |                           |                  |      |       |     |                  |                |                |     |            |                 |  |                 |                 |                 |
|        |           |          |                           |                  |      |       |     |                  |                |                |     |            |                 |  |                 |                 |                 |
|        |           |          |                           |                  |      |       |     |                  |                |                |     |            |                 |  |                 |                 |                 |
|        |           |          |                           |                  |      |       |     |                  |                |                |     |            |                 |  |                 |                 |                 |
|        | ✓         | ✓        | ✓                         | ✓                | ✓    | ✓     | ✓   |                  | ✓*             |                |     |            |                 |  |                 |                 |                 |
|        |           |          |                           |                  |      |       |     |                  | ✓•             | ✓•             | ✓•  | ✓•         |                 |  |                 |                 |                 |
|        |           |          |                           |                  |      |       |     |                  | ✓*             | ✓•             | ✓•  | ✓•         | ✓*              |  |                 |                 |                 |
|        |           |          |                           |                  |      |       |     | ✓                |                |                |     |            |                 |  | ✓               | ✓               | ✓               |
|        |           |          |                           |                  |      |       |     | ✓                |                |                |     |            |                 |  | €               | ✓               | ✓               |
|        | ✓         | ✓        | ✓                         | ✓                | ✓    | ✓     | ✓   |                  |                | ✓‡             | ✓‡  | ✓‡         |                 |  | ✓∅              |                 |                 |
|        | ✓‡        | ✓‡       |                           | €                | ✓‡   | €     | ✓‡  |                  |                | ✓‡             | ✓‡  | ✓‡         |                 |  | ✓‡              | ✓‡              | ✓‡              |
|        |           |          |                           |                  |      |       |     |                  |                |                |     |            |                 |  | ✓               | ✓               |                 |

LEGEND: \* Double Stick † Permanent ‡ Vertical € Contact Manufacturer • Release ∅ Up to 2.5mm

# PRESSURE SENSITIVE AND WET SET ADHESIVE



12kg



ARDEX AF 145 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Can also be used as a wet set adhesive
- Ready to receive floorcoverings in as little as 20 minutes
- Can receive vinyl sheet up to 80 minutes after airing
- Excellent early and long term adhesive strength
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 48m<sup>2</sup>


Suitable for:

- ✓ Vinyl Sheet
- ✓ Cushioned Vinyl
- ✓ Luxury Vinyl Tiles
- ✓ Vinyl Composition Tiles



Image courtesy of Lifestyle Floors

## Installation Schedule:



LEGEND:

AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.


WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

OPEN TIME:

The combination of airing and working time.





For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# PRESSURE SENSITIVE CONTRACT ADHESIVE



10kg



ARDEX AF 148 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Extended 3 hour working time
- High grab and exceptional final bond strength
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 52m<sup>2</sup>


Suitable for:

- ✓ Vinyl Sheet
- ✓ Cushioned Vinyl
- ✓ Vinyl Composition Tiles
- ✓ Luxury Vinyl Tiles



## Installation Schedule:

### Pressure Sensitive



#### LEGEND:

##### AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.


##### WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

##### OPEN TIME:

The combination of airing and working time.





For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# VINYL ADHESIVE



14 kg



ARDEX AF 165 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- High initial tack
- Can receive floorcoverings up to 30 minutes after airing
- Excellent early and long term adhesive strength
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 67m<sup>2</sup>

Suitable for:



Vinyl Sheet



Cushioned Vinyl




A1  
Up to 67m<sup>2</sup>

CV Flooring

A2  
Up to 56m<sup>2</sup>

Vinyl Sheet/CV Flooring/LVT

Installation Schedule:



LEGEND:

AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.

WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.




For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.





# LUXURY VINYL TILE ADHESIVE



ARDEX AF 175 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Fibre reinforced to offer the following benefits:
  - Minimises lateral movement during installation
  - Eliminates adhesive squeeze between tiles and planks
  - Improved indentation resistance
- Install tiles and planks after just 5 minutes
- Walk on after 2 hours
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 48m<sup>2</sup>

## Suitable for:

- ✓ Luxury Vinyl Tiles and Planks
- ✓ Cushioned Vinyl
- ✓ Vinyl Composition Tiles



Image courtesy of Lifestyle Floors

## Installation Schedule:



### LEGEND:

#### AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.

#### WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

#### OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.



For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# LOW EMISSION CARPET ADHESIVE



14 kg



ARDEX AF 325 meets the requirement guidelines for the EMICODE license "EC1 PLUS" achieving the lowest possible emission limits.

- Excellent early grab means that carpets can be installed in as little as 5 minutes
- Up to 30 minute extended working time
- Rapid strength development
- High temperature resistance, suitable for use over underfloor heating systems
- Ideal for use with the double stick method, in conjunction with ARDEX AF 825 Tackifier
- Solvent free
- Low odour
- Covers up to 35m<sup>2</sup>

Suitable for:

- |             |                             |                    |
|-------------|-----------------------------|--------------------|
| ✓ Woven     | ✓ Gel Foam                  | ✓ Secondary Backed |
| ✓ Actionbac | ✓ Needle Punch/Fibre Bonded | ✓ Felt             |
| ✓ Latex     | ✓ PVC                       |                    |



Installation Schedule:



LEGEND:

AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.

WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorpency of the subfloor and site conditions.





For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.





# TACKIFIER



10kg



ARDEX AF 825 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Install floorcoverings in as little as 10 minutes, or up to 24 hours after application
- Instant release allows worn or damaged tiles to be removed easily
- Suitable for raised access flooring
- High temperature resistance, suitable for use over underfloor heating systems
- Extremely low odour
- Solvent free
- Covers up to 125m<sup>2</sup>

Suitable for:



Bitumen Backed Carpet Tiles




Gel Backed Carpet Tiles



PVC Carpet Tiles



Installation Schedule:



LEGEND:

AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.

WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.



For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.





# HIGH GRAB TACKIFIER



10kg



ARDEX AF 835 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Can be used as a permanent or release bond adhesive
- Ideal for carpet underlays and carpet tiles
- Ideal for use with the double stick method, in conjunction with ARDEX AF 325 Low Emission Carpet Adhesive
- Low odour and very low emissions
- High temperature resistance, suitable for use over under-floor heating systems
- Covers up to 71m<sup>2</sup>

Suitable for:

- ✓ Bitumen Backed Carpet Tiles
- ✓ Carpet Underlay\*

- ✓ Gel Backed Carpet Tiles
- \*Double Stick

- ✓ PVC Carpet Tiles



Installation Schedule:



LEGEND:

AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.

WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.



For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# HEAVY DUTY ADHESIVE - ONE COMPONENT



7 kg



ARDEX AF 2575 PLUS meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Moisture, weather and water resistant
- Suitable for internal and external use
- High temperature resistance, for use in areas of direct sunlight e.g. conservatories
- Very high bond strength, for use in high load areas
- Zero waste – ready mixed and resealable
- Very low emissions
- Solvent free
- Suitable for installing LVT to walls
- Covers up to 23m<sup>2</sup>


Suitable for:

- |                           |                          |                          |
|---------------------------|--------------------------|--------------------------|
| ✓ Artificial grass        | ✓ Luxury Vinyl Tiles     | ✓ Vinyl Sheet            |
| ✓ Vinyl Composition Tiles | ✓ Rubber Sheet up to 4mm | ✓ Rubber Tiles up to 9mm |



|  |
|--|
| <b>A1</b><br>Up to 23m <sup>2</sup><br>LVT/Vinyl/CV Flooring/Rubber Flooring |
| <b>A2</b><br>Up to 19m <sup>2</sup><br>LVT/Vinyl/CV Flooring/Rubber Flooring |
| <b>B1</b><br>Up to 16m <sup>2</sup><br>Rubber Flooring with sanded back >3.2 |

Installation Schedule:



LEGEND:

**AIRING TIME:**

The time the adhesive must be left open before applying the floorcovering.

**WORKING TIME:**


The time in which the adhesive can receive the floorcovering, after the initial airing time.

**OPEN TIME:**

The combination of airing and working time.

\*Times dependent on the absorptency of the subfloor and site conditions.





For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# HEAVY DUTY ADHESIVE - TWO COMPONENT



6kg



ARDEX AF 2525 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Moisture, weather and water resistant
- Suitable for internal and external use
- High temperature resistance, for use in areas of direct sunlight e.g. conservatories
- Very high bond strength, for use in high load areas
- Easy to mix and apply
- Very low emissions
- Solvent free
- Covers up to 20m<sup>2</sup>

Suitable for:


- |                           |                          |               |
|---------------------------|--------------------------|---------------|
| ✓ Artificial grass        | ✓ Luxury Vinyl Tiles     | ✓ Vinyl Sheet |
| ✓ Vinyl Composition Tiles | ✓ Rubber Tiles up to 9mm | ✓ Wood        |



|   |
|---|
| <b>A2</b><br>Up to 20m <sup>2</sup>                         |
| Vinyl Sheet/LVT/CV Flooring/<br>Rubber                      |
| <b>B1</b><br>Up to 13m <sup>2</sup>                         |
| Linoleum/Other Flooring with<br>little Structure on Backing |
| <b>B2</b><br>Up to 12m <sup>2</sup>                         |
| Heavily Structured Backing                                  |

*Note: For wood, please consult the flooring manufacturer for correct trowel size.*

Installation Schedule:



LEGEND:

**AIRING TIME:**

The time the adhesive must be left open before applying the floorcovering.

**WORKING TIME:**

The time in which the adhesive can receive the floorcovering, after the initial airing time.

**OPEN TIME:**

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.





For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.





# UNIVERSAL ADHESIVE



14 kg 6 kg



ARDEX AF 2365 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

■ Suitable for installing all main floorcovering types:

- Luxury Vinyl Tiles and Planks
- Textiles
- Rubber up to 2.5mm
- Linoleum
- Vinyl Sheet
- Cushioned Vinyl

■ High temperature resistance, suitable for use over underfloor heating systems

■ Solvent free


■ Covers up to 67m<sup>2</sup>

Suitable for:

- |                      |                      |                   |
|----------------------|----------------------|-------------------|
| ✓ Luxury Vinyl Tiles | ✓ Rubber up to 2.5mm | ✓ Vinyl Sheet     |
| ✓ Textiles           | ✓ Linoleum           | ✓ Cushioned Vinyl |



Installation Schedule:



LEGEND:

**AIRING TIME:**

The time the adhesive must be left open before applying the floorcovering.

**WORKING TIME:**

The time in which the adhesive can receive the floorcovering, after the initial airing time.

**OPEN TIME:**

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.



For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.





# SOLVENT FREE CONTACT ADHESIVE



2.5kg



ARDEX AF 635 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Solvent free formulation
- Very low emission
- Easy to apply with a short-piled roller or paintbrush
- Long working time
- Long bond and high initial tack
- Floors can receive foot traffic immediately after application
- Covers up to 25m<sup>2</sup>


## Suitable for:

- |                      |                           |                         |
|----------------------|---------------------------|-------------------------|
| ✓ Vertical Surfaces  | ✓ Cushioned Vinyl         | ✓ Linoleum              |
| ✓ Luxury Vinyl Tiles | ✓ Coving/Skirting         | ✓ Carpet & Carpet Tiles |
| ✓ Vinyl Sheet        | ✓ Vinyl Composition Tiles | ✓ Rubber Flooring       |



If preferred, the floorcovering or profile can be pre-coated the day before installation. The open time for flooring/profiles already pre-coated on the previous day into the newly applied film is approximately 90 minutes. The surfaces coated/pre-coated with ARDEX AF 635 must be placed together within the open time of 24 hours.

## Installation Schedule:



## LEGEND:

### AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.

### WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

### OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.



For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# RUBBER FLOORING ADHESIVE



12kg



ARDEX AF 275 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- Fibre reinforced to offer the following benefits:
  - Maximum bond strength
  - Minimal lateral movement during installation
  - Eliminates adhesive squeeze between tile joins
  - Improved indentation resistance
- Ready to receive rubber floorcoverings in as little as 5 minutes
- Suitable for installing rubber flooring up to 4mm thick
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 40m<sup>2</sup>

Suitable for:



Sheet up to 4mm



Tiles up to 4mm



Installation Schedule:



LEGEND:

**AIRING TIME:**

The time the adhesive must be left open before applying the floorcovering.

**WORKING TIME:**


The time in which the adhesive can receive the floorcovering, after the initial airing time.

**OPEN TIME:**

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.





For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.



# LINOLEUM ADHESIVE



14 kg



ARDEX AF 785 meets the requirement guidelines for the EMICODE licence 'EC1 PLUS', achieving the lowest possible emission limits.

- High initial grab
- Excellent adhesive transfer to the floorcovering backing
- Excellent early and long term adhesive strength
- High temperature resistance, suitable for use over underfloor heating systems
- Solvent free
- Covers up to 39m<sup>2</sup>

Suitable for:



Jute/Hessian Backed



Polyester Backed Tiles



Polyester Backed Sheet



Installation Schedule:



LEGEND:

AIRING TIME:

The time the adhesive must be left open before applying the floorcovering.


WORKING TIME:

The time in which the adhesive can receive the floorcovering, after the initial airing time.

OPEN TIME:

The combination of airing and working time.

\*Times dependent on the absorbency of the subfloor and site conditions.



For further information on our range of Moisture Control products and Levelling and Smoothing Compounds, please refer to pages 32-33, visit [www.ardex.co.uk](http://www.ardex.co.uk) or contact ARDEX Technical Services on 01440 714939.





# CHOOSE YOUR SOLUTION

All ARDEX Flooring Adhesives are designed to work with our range of Levelling and Smoothing Compounds, in both commercial and domestic environments, and have been developed and tested to be fully compatible with the most commonly used floorcovering types.

## DRY FLOORS (RH below 75%)



PRIMING



LEVELLING & SMOOTHING



NO PRIMING  
REQUIRED

LEVELLING & SMOOTHING



FLOORING ADHESIVES



ARDEX offer a full system solution, enabling you to carry out the correct preparation on the most common subfloor types, helping to ensure the perfect flooring installation every time.

## DAMP FLOORS (RH above 75%)



MOISTURE CONTROL



RH 75% - 95%  
(Functioning DPM)

LEVELLING & SMOOTHING



MOISTURE CONTROL



RH 75% - 98%  
(No functioning DPM)

LEVELLING & SMOOTHING



FLOORING ADHESIVES







## TECHNICAL SUPPORT


WHEN AND WHERE YOU NEED IT MOST



TECHNICAL  
ADVICE



SITE  
SUPPORT



MOISTURE  
TESTS



SPECIFICATION  
WRITING



TRAINING

OUR EXPERIENCED TEAM ARE AVAILABLE NATIONWIDE TO OFFER ADVICE,  
SUPPORT AND TRAINING, NOT JUST OVER THE PHONE,  
BUT IN PERSON AND ON-SITE.



ARDEX don't just manufacture High Performance Building products, we recognise the importance of providing gold standard technical advice and support. We understand your needs differ from project to project, and can often require on-site support, which is why we offer a more mobile, local technical support network.



### TECHNICAL ADVICE

We're on hand to offer advice and product recommendations, in line with British Standards codes of practice, via telephone, email, video call and our social media channels.



### SITE SUPPORT

Our highly experienced Technical Service team are available to attend your site, offering site assessments, advice and guidance on the best use of our products and systems for your project.



### MOISTURE TESTS

Many problems which occur on site are the result of moisture in the subfloor, so it's essential that the final floorcovering is protected from the passage of moisture from below. Our team can perform on-site Hygrometer tests, explain the results and recommend the best moisture control system for your installation.

We're also on hand to perform additional site tests such as the **BRE Screed Test**, which is designed to measure the soundness of a sand/cement floor screed.



### SPECIFICATION WRITING

We work closely with architects, specifiers, contractors and floorcovering manufacturers to ensure the most suitable specification for your project. When specifying ARDEX you can rely on our expert team for on-going support at every stage of your project, including a rapid response to specification writing.



### TRAINING

ARDEX offer a range of courses at our purpose built Academies in Suffolk and Stoke-on-Trent. Alternatively we can tailor training to meet your specific needs and deliver it at a location of your choice.

#### ARDEX Flooring Installation Courses:

- Subfloor Preparation
- Subfloor Preparation & LVT Installation
- Intermediate Subfloor Preparation
- Subfloor Preparation & Introduction into Installing Safety Flooring in a Wet Room
- Identification and Preparation of an Anhydrite/ Calcium Sulphate Screed

To view our latest courses or to book your place visit [www.ardex.co.uk/training](http://www.ardex.co.uk/training)





ARDEX UK Limited, Homefield Road, Haverhill, Suffolk CB9 8QP  
Tel: 01440 714939 Email: [info@ardex.co.uk](mailto:info@ardex.co.uk)  
[www.ardex.co.uk](http://www.ardex.co.uk) [www.ardexcpdacademy.com](http://www.ardexcpdacademy.com)

