



DECLARATION OF PERFORMANCE
in accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No 574/2014

No. **41956**

Unique identification code of the product type: **41956 ARDEX 4x4 CREAM WHITE, EN 12004:C2TE-S1**

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Improved, deformable cementitious adhesive with reduced slip and extended open time, for indoor and outdoor tiling

Name, registered trade name or registered trademark and contact address of the manufacturer:

ARDEX Cemento S.A.
Pol. Ind. Pla de Llerona
C./Holanda, 18
E-08520 Les Franqueses del Vallès (Barcelona)
España

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
Reaction to fire: System 4

Harmonised standard:

EN 1200:2007+A1:2012

Notified body:

LGAI TECHNOLOGICAL CENTER, S.A./Applus with identification number 370.

Declared Performance:

Essential Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification
Reaction to fire:	E	System 4	EN 12004:2007+A1:2012
Bond strength			
Initial tensile adhesion strength:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Durabilidad			
Tensile adhesion strength after heat ageing:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Tensile adhesion strength after water immersion:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Release of dangerous substances:	See Safety Data Sheet		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Xavier Galobardes
Manager of Operations, production site ASA



Joan Bo
Head of Technical Department, production site ASA

Les Franqueses del Vallès, 30th May 2023

(Place and date of issue)

Additional Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification
Special Characteristics			
Open time:	≥ 0.5 N/mm ² after at least 30 minutes	System 3	EN 12004:2007+A1:2012
Slip:	≤ 0.5 mm	System 3	EN 12004:2007+A1:2012
Transverse deformation:	≥ 2.5mm y ≤ 5 mm	System 3	EN 12004:2007+A1:2012