



DECLARATION OF PERFORMANCE
in accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No 574/2014

Product: **ARDEX ADHESIVO 4x4 FAST**
No. **46976**

Unique identification code of the product type:

46976 ARDEX 4x4 FAST
EN 12004:C2FTE-S1

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Rapid deformable cementitious adhesive with reduced slip and extended open time, for indoor and outdoor tiling

Name, registered trade name or registered trademark and contact address of the manufacturer:

ARDEX Cemento S.A.
Pol. Ind. Pla.de Llerona
C./Holanda, 18
E-08520 Les Franqueses del Vallès (Barcelona)
España

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

Harmonized standard: **EN 12004:2007+A1:2012**

Notified body:

LGAI TECHNOLOGICAL CENTER, S. A./Applus , identification number **0370**



Declared Performance:

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire:	E	EN 12004:2007+A1:2012
Release of dangerous substances:	See Safety Data Sheet	
Bond strength	Performance	Harmonized Technical Specification
Initial tensile adhesion strength:	$\geq 1.0 \text{ N/mm}^2$	EN 12004:2007+A1:2012
Early tensile adhesion:	$\geq 0.5 \text{ N/mm}^2$	EN 12004:2007+A1:2012
Durability	Performance	Harmonized Technical Specification
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$	EN 12004:2007+A1:2012
Tensile adhesion strength after heat ageing:	$\geq 1.0 \text{ N/mm}^2$	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles:	$\geq 1.0 \text{ N/mm}^2$	EN 12004:2007+A1:2012

Special Characteristics	Performance	Harmonized Technical Specification
Open time (30 min):	$\geq 0.5 \text{ N/mm}^2$	EN 12004:2007+A1:2012
Slip:	$\leq 0,5 \text{ mm}$	EN 12004:2007+A1:2012
Transverse deformation:	$\geq 2.5 \text{ mm y } < 5 \text{ mm}$	EN 12004:2007+A1:2012

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Xavier Galobardes
 Manager of Operations, production site ASA

Vanessa Serra
 Head of Laboratory, production site ASA

Les Franqueses del Vallès, 15.05.2025

(Place and date of issue)